

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 108 876 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
20.06.2001 Bulletin 2001/25

(51) Int Cl.7: F02D 41/40, F01N 3/20,
F02D 21/08

(21) Application number: 00101967.8

(22) Date of filing: 01.02.2000

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Ito, Takekazu
Toyota-shi, Aichi-ken 471-8571 (JP)
• Sasaki, Shizuo
Toyota-shi, Aichi-ken 471-8571 (JP)

(30) Priority: 16.12.1999 JP 35771899


(71) Applicant: TOYOTA JIDOSHA KABUSHIKI
KAISHA
Aichi-ken 471-8571 (JP)

(74) Representative:
Pellmann, Hans-Bernd, Dipl.-Ing. et al
Patentanwaltsbüro
Tiedtke-Bühling-Kinne & Partner
Bavariaring 4-6
80336 München (DE)

(54) Internal combustion engine

(57) An engine comprising an exhaust gas after-treatment device arranged in an exhaust passage of the engine, which raises the temperature of the exhaust gas after-treatment device by making selective use of a first injection pattern injecting only main fuel and delaying the injection timing of the main fuel Q_R , a second injection pattern injecting auxiliary fuel Q_v near top dead center of the suction stroke and delaying the injection timing of the main fuel Q_R , and a third injection pattern injecting auxiliary fuel Q_v and Q_p before injection of the main fuel and after injection and delaying the injection timing of the main fuel Q_R .

Fig.1



Description

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to an internal combustion engine.

2. Description of the Related Art

[0002] As an exhaust gas after-treatment device arranged in the exhaust passage of an engine, there is known an NO_x absorbent which absorbs the NO_x in exhaust gas when the air-fuel ratio of the exhaust gas is lean and releases and reduces the absorbed NO_x when the air-fuel ratio of the exhaust gas becomes the stoichiometric air-fuel ratio or rich. In such an exhaust gas after-treatment device, the air-fuel ratio of the exhaust gas is temporarily made rich before the NO_x absorption capability of the NO_x absorbent becomes saturated so as to make all of the NO_x absorbed in the NO_x absorbent be released from the NO_x absorbent and reduced.

[0003] Fuel, however, contains sulfur. Therefore, the exhaust gas contains SO_x. This SO_x is also absorbed by the NO_x absorbent. This SO_x is not released from the NO_x absorbent just by making the air-fuel ratio of the exhaust gas rich. To make the SO_x be released from the NO_x absorbent, it is necessary to raise the temperature of the NO_x absorbent. Therefore, there is known an internal combustion engine wherein when the temperature of the NO_x absorbent should be raised, additional fuel is injected in the expansion stroke or exhaust stroke in addition to the main fuel injected during the suction stroke and that additional fuel is made to burn in the NO_x absorbent so as to raise the temperature of the NO_x absorbent (see Japanese Unexamined Patent Publication (Kokai) No. 9-32619).

[0004] In this way, in an internal combustion engine, it is sometimes necessary to raise the temperature of the exhaust gas after-treatment device. In this case, in an internal combustion engine, there are sometimes cases where it is necessary to rapidly raise the temperature of the exhaust gas after-treatment device. Further, there are sometimes cases where conversely it is necessary to slowly raise the temperature of the exhaust gas after-treatment device. That is, it becomes necessary to be able to change the temperature raising rate of the exhaust gas after-treatment device in accordance with demand. In the above known internal combustion engine, however, when raising the temperature of the exhaust gas after-treatment device, a predetermined injection pattern determined by the operating state of the engine was used. As a result, there was the problem that it was not possible to freely change the temperature raising rate of the exhaust gas after-treatment device in accordance with demand.

SUMMARY OF THE INVENTION

[0005] An object of the present invention is to provide an internal combustion engine capable of raising a temperature of an exhaust gas after-treatment device at a temperature raising rate which is required for the exhaust gas after-treatment device.

[0006] According to the present invention, there is provided an internal combustion engine having a combustion chamber and an exhaust passage, the engine comprising fuel injection means for injecting an auxiliary fuel into the combustion chamber, in addition to a main fuel, in accordance with necessity to produce unburned hydrocarbons; an exhaust gas after-treatment device arranged in the exhaust passage, a temperature of the exhaust gas after-treatment device rising when a temperature of exhaust gas rises and rising when unburned hydrocarbons are supplied to the exhaust gas after-treatment device; and injection control means for retarding an injection timing of the main fuel when the temperature of the exhaust gas after-treatment device should rise, as compared with the case where the temperature of the exhaust gas after-treatment device should not rise, at least two injection patterns, which are different in at least one of an amount of retardation of the injection timing of the main fuel and injection timing of the auxiliary fuel, being determined in advance to raise the temperature of the exhaust gas after-treatment device, the injection control means choosing any one of the injection patterns in accordance with a demand for a temperature raising rate of the exhaust gas after-treatment device and injecting fuel in accordance with the chosen injection pattern when the temperature of the exhaust gas after-treatment device should rise.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] The present invention will be more fully understood from the description of preferred embodiments of the invention set forth below, together with the accompanying drawings, in which:

Fig. 1 is an overview of an internal combustion engine;

Figs. 2A and 2B are views of a required torque;

Fig. 3 is a view of a throttle valve degree of opening and an EGR control valve degree of opening etc.;

Figs. 4A and 4B are views of maps of injection amounts etc.;

Figs. 5A and 5B are views of maps of target degrees of opening of a throttle valve etc.;

Figs. 6A and 6B are views for explaining an absorption and release action of NO_x;

Fig. 7 is a view of a map of an amount of NO_x absorption per unit time;

Figs. 8 to 10 are views of injection timings;

Fig. 11 is a view of an injection start timing;

Fig. 12 is a view of injection patterns;

Figs. 13A and 13B are time charts of temperature changes of an NO_x absorbent;

Fig. 14 is a view of changes in the throttle valve degree of opening etc. at the time of control for release of SO_x;

Fig. 15 is a view of the amounts of main fuel and auxiliary fuel;

Figs. 16A and 16B are views of maps of the target degree of opening etc. of a throttle valve;

Fig. 17 is a view of changes in the throttle valve degree of opening etc. at the time of control for SO_x release;

Fig. 18 is a view of changes in the throttle valve degree of opening etc. at the time of control for NO_x release;

Fig. 19 is a view of the amounts of main fuel and auxiliary fuel;

Fig. 20 is a flow chart of the processing of an NO_x releasing flag and SO_x releasing flag;

Fig. 21 is a flow chart of the control of the operation of the engine;

Fig. 22 is a flow chart of the control for raising the temperature;

Fig. 23 is an overview of another embodiment of an internal combustion engine;

Fig. 24 is a view of an injection pattern;

Fig. 25 is a flow chart of the control of the operation of the engine; and

Fig. 26 is a flow chart of the control for raising the temperature.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0008] Referring to Fig. 1, 1 shows an engine body, 2 a cylinder block, 3 a cylinder head, 4 a piston, 5 a combustion chamber, 6 an electrically controlled fuel injector, 7 an intake valve, 8 an intake port, 9 an exhaust valve, and 10 an exhaust port. The intake port 8 is connected through a corresponding intake tube 11 to a surge tank 12. The surge tank 12 is connected through an intake duct 13 to a compressor 15 of an exhaust turbocharger 14. A throttle valve 17 driven by a step motor 16 is arranged in the intake duct 13.

[0009] On the other hand, the exhaust port 10 is connected through an exhaust manifold 18 and exhaust tube 19 to an exhaust turbine 20 of the exhaust turbocharger 14. The outlet of the exhaust turbine 20 is connected to an exhaust gas after-treatment device 21. In the embodiment shown in Fig. 1, the exhaust gas after-treatment device 21 is comprised of an NO_x absorbent 22 and a casing 23 housing the NO_x absorbent 22.

[0010] The exhaust manifold 18 and the surge tank 12 are connected to each other through an exhaust gas recirculation (EGR) passage 24. An EGR control valve 25 is arranged in the EGR passage 24. Each fuel injector 6 is connected through a fuel supply line 26 to a fuel reservoir, that is, a so-called common rail 27. Fuel is

supplied into this common rail 27 from an electronically controlled variable discharge fuel pump 28. The fuel supplied into the common rail 27 is supplied through the fuel supply lines 26 to the fuel injectors 6. The common rail 27 has mounted in it a fuel pressure sensor for detecting the fuel pressure in the common rail 27. The amount of discharge of the fuel pump 28 is controlled based on the output signal of the fuel pressure sensor 29 so that the fuel pressure in the common rail 27 becomes a target fuel pressure.

[0011] The electronic control unit 30 is comprised of a digital computer and is provided with a read only memory (ROM) 32, a random access memory (RAM) 33, a microprocessor (CPU) 34, an input port 35, and an output port 36 connected with each other by a bidirectional bus 31. Downstream of the NO_x absorbent 22 is arranged a temperature sensor 39 for detecting the temperature of the NO_x absorbent 22. The output signals of the temperature sensor 39 and the fuel pressure sensor 29 are input through corresponding A/D converters 37 to the input port 35. The accelerator pedal 40 has connected to it a load sensor 41 for generating an output voltage proportional to the amount of depression of the accelerator pedal 40. The output voltage of the load sensor 41 is input through a corresponding AD converter 37 to the input port 35. Further, the input port 35 has connected to it a crank angle sensor 42 for generating an output pulse every time the crank shaft rotates by for example 30 degrees. On the other hand, the output port 36 has connected to it through corresponding drive circuits 38 the fuel injectors 6, step motor 16, EGR control valve 25, and fuel pump 28.

[0012] Figure 2A shows the relationship between the required torque TQ, the amount of depression L of the accelerator pedal 40, and the engine rotational speed N. Note that in Fig. 2A, the curves show equivalent torque curves. The curve shown by TQ=0 shows that the torque is zero, while the remaining curves have gradually higher required torques in the order of TQ=a, TQ=b, TQ=c, and TQ=d. The required torques TQ shown in Fig. 2A are stored in the ROM 32 in advance in the form of a map as a function of the amount of depression L of the accelerator pedal 40 and the engine rotational speed N as shown in Fig. 2B. In this embodiment according to the present invention, the required torque TG is first calculated in accordance with the amount of depression L of the accelerator pedal 40 and the engine rotational speed N from the map shown in Fig. 2B and then the amount of fuel injection etc. are calculated based on the required torque TQ.

[0013] Figure 3 shows the amount of injection Q at the time of ordinary operation, the injection start timing θ_S , the degree of opening ST of the throttle valve 17, the degree of opening SE of the EGR control valve 25, the mean air-fuel ratio A/F of the air-fuel mixture in the combustion chamber 5, and the EGR rate (amount of EGR gas/(amount of intake air + amount of EGR gas)). Note that in Fig. 3, the abscissa shows the required torque

TQ.

[0014] As shown in Fig. 3, at the time of ordinary operation, the injection start timing θ_S is made before top dead center of the compression stroke. On the other hand, the EGR rate falls the higher the required torque TQ. The ER rate becomes zero in the region of the high required torque TQ. The degree of opening ST of the throttle valve 17 and the degree of opening SE of the EGR control valve 25 are made to change so that the EGR rate changes as explained above. That is, the degree of opening ST of the throttle valve 17 is made to increase as the required torque TQ becomes higher in the region of a low required torque TQ. The throttle valve 17 is made to fully open when the required torque TQ becomes further higher. Further, the EGR valve 25 is made to fully open in the region of a low required torque TQ and made to completely close in the region of a high required torque TQ. Between the region of the low required torque TQ and the region of the high required torque TQ, the degree of opening SE of the EGR valve 25 is gradually reduced as the required torque TQ becomes higher. Further, it is made smaller when the mean air-fuel ratio A/F in the combustion chamber 5 is lean and the required torque TQ becomes higher.

[0015] The amount of injection Q, the injection start timing θ_S , the degree of opening ST of the throttle valve 17, and the degree of opening SE of the EGR control valve 25 are not functions of just the required torque TQ, but are functions of the required torque TQ and the engine rotational speed N. In this embodiment according to the present invention, as shown in Fig. 4A, the amount of injection Q is stored in advance in the ROM 32 in the form of a map as a function of the required torque TQ and the engine rotational speed N. As shown in Fig. 4B, the injection start timing θ_S is also stored in advance in the ROM 32 in the form of a map as a function of the required torque TQ and the engine rotational speed N. Further, the degree of opening ST of the throttle valve 17, as shown in Fig. 5A, is stored in advance in the ROM 32 in the form of a map as a function of the required torque TQ and the engine rotational speed N, while the degree of opening SE of the EGR control valve 25, as shown in Fig. 5B, is stored in advance in the ROM 32 in the form of a map as a function of the required torque TQ and the engine rotational speed N.

[0016] Now, the NO_x absorbent 22 housed in the casing 23 in Fig. 1 is comprised of for example alumina as a carrier and, carried on that carrier, for example, at least one element selected from potassium K, sodium Na, lithium Li, cesium Cs, and other alkali metals, barium Ba, calcium Ca and other alkali earth metals, and lanthanum La, yttrium Y, and other rare earths plus a rare metal such as platinum. If the ratio of the air and fuel (hydrocarbons) supplied into the engine intake passage, combustion chamber 5, and exhaust passage upstream of the NO_x absorbent 22 is referred to as the air fuel ratio of the exhaust gas flowing into the NO_x absorbent 22, then the NO_x absorbent 22 performs an NO_x ab-

sorption and release action in which it absorbs NO_x when the air-fuel ratio of the inflowing exhaust gas is lean while releases the absorbed NO_x when the air-fuel ratio of the inflowing exhaust gas becomes the stoichiometric air-fuel ratio or rich.

[0017] If this NO_x absorbent 22 is placed in the engine exhaust passage, the NO_x absorbent 22 will in actuality perform an NO_x absorption and release action, but there are portions of the detailed mechanism of this absorption and release action which are still not clear. This absorption and release action, however, is considered to be performed by the mechanism shown in Figs. 6A and 6B. Next, this mechanism will be explained taking as an example the case of carrying platinum Pt and barium Ba on the carrier, but the same mechanism applies even if using another precious metal and alkali metal, alkali earth, or rare earth.

[0018] In the internal combustion engine shown in Fig. 1, combustion is performed when the mean air-fuel ratio in the combustion chamber 5 is in a lean state. When combustion is performed with the mean air-fuel ratio in a lean state in this way, the concentration of oxygen in the exhaust gas is high. At this time, as shown in Fig. 6A, the oxygen O_2 deposits on the surface of the platinum Pt in the form of O_2^- or O^{2-} . On the other hand, the NO in the inflowing exhaust gas reacts with the O_2^- or O^{2-} on the surface of the platinum Pt to become NO_2 ($2\text{NO} + \text{O}_2 \rightarrow 2\text{NO}_2$). Next, part of the produced NO_2 is oxidized on the platinum Pt and absorbed in the absorbent and diffuses inside the absorbent in the form of nitrate ions NO_3^- as shown in Fig. 6A while bonding with the barium oxide BaO. The NO_x is absorbed in the NO_x absorbent 22 in this way. So long as the concentration of oxygen in the inflowing exhaust gas is high, NO_2 is produced on the surface of the platinum Pt. So long as the NO_x absorption capability of the absorbent does not become saturated, the NO_2 is absorbed in the absorbent and nitrate ions NO_3^- are produced.

[0019] On the other hand, when the air-fuel ratio of the inflowing exhaust gas is made rich, the concentration of oxygen in the inflowing exhaust gas falls and as a result the amount of production of NO_2 on the surface of the platinum Pt falls. If the amount of production of NO_2 falls, the reaction proceeds in the reverse direction ($\text{NO}_3^- \rightarrow \text{NO}_2$) and therefore the nitrate ions NO_3^- in the absorbent are released from the absorbent in the form of NO_2 . At this time, the NO_x released from the NO_x absorbent 22 reacts with the large amount of unburnt hydrocarbons and carbon monoxide contained in the inflowing exhaust gas to be reduced as shown in Fig. 6B. In this way, when there is no longer any NO_2 present on the surface of the platinum Pt, NO_2 is successively released from the absorbent. Therefore, if the air-fuel ratio of the inflowing exhaust gas is made rich, the NO_x will be released from the NO_x absorbent 22 in a short time and, further, the released NO_x will be reduced, so no NO_x will be discharged into the atmosphere.

[0020] Note that in this case, even if the air-fuel ratio

of the inflowing exhaust gas is made the stoichiometric air-fuel ratio, NO_x will be released from the NO_x absorbent 22. When the air-fuel ratio of the inflowing exhaust gas is made the stoichiometric air-fuel ratio, however, the NO_x will be released from the NO_x absorbent 22 only gradually, so a somewhat long time will be required for having all of the NO_x absorbed in the NO_x absorbent 22 be released.

[0021] There are, however, limits to the NO_x absorption capability of the NO_x absorbent 22. It is necessary to release the NO_x from the NO_x absorbent 22 before the NO_x absorption capability of the NO_x absorbent 22 becomes saturated. Therefore, it is necessary to estimate the amount of NO_x absorbed in the NO_x absorbent 22. Therefore, in this embodiment of the present invention, the amount of NO_x absorption AX per unit time is found in advance in the form of the map shown in Fig. 7 as a function of the required torque TQ and the engine rotational speed N. The amount ΣNOX of NO_x absorbed in the NO_x absorbent 22 is estimated by cumulative addition of the amount of NO_x absorption AX. In this embodiment according to the present invention, when the amount ΣNOX of NO_x absorption exceeds a predetermined maximum allowable value, the air-fuel ratio of the inflowing exhaust gas is temporarily made rich so as to make the NO_x be released from the NO_x absorbent 22.

[0022] As explained at the start, however, exhaust gas contains SO_x and the NO_x absorbent 22 absorbs not only NO_x , but also SO_x . The mechanism of absorption of SO_x into the NO_x absorbent 22 is believed to be the same as the mechanism of absorption of NO_x .

[0023] That is, in the same way as explained with respect to the mechanism of absorption of NO_x , giving an explanation taking as an example the case of carrying on the carrier platinum PT and barium Ba, as explained above, when the air-fuel ratio of the inflowing exhaust gas is lean, oxygen O_2 deposits on the surface of the platinum Pt in the form of O_2^- or O^{2-} . On the other hand, the SO_2 in the inflowing exhaust gas reacts with the O_2^- or O^{2-} on the surface of the platinum Pt to become SO_3 . Next, part of the produced SO_3 is oxidized on the platinum Pt and absorbed in the absorbent and diffuses inside the absorbent in the form of sulfate ions SO_4^{2-} while bonding with the barium oxide BaO to produce the stable sulfate BaSO_4 .

[0024] This sulfate BaSO_4 , however, is stable and hard to decompose. Even if the air-fuel ratio of the inflowing exhaust gas is made rich for release of the NO_x from the NO_x absorbent 22, the sulfate BaSO_4 does not decompose and remains as it is. Therefore, along with the passage of time, the sulfate BaSO_4 in the NO_x absorbent 22 increases and therefore along with time the amount of NO_x which the NO_x absorbent 22 can absorb falls.

[0025] The sulfate BaSO_4 , however, decomposes when the temperature of the NO_x absorbent 22 exceeds a certain temperature determined by the NO_x absorbent 22, for example, about 600°C . If the air-fuel ratio of the

exhaust gas flowing into the NO_x absorbent 22 at this time is made the stoichiometric air-fuel ratio or rich, the SO_x will be released from the NO_x absorbent 22. Making the SO_x be released from the NO_x absorbent 22, however, requires a considerably long time compared with the case of releasing the NO_x from the NO_x absorbent 22. Giving one example, it is possible to release all of the NO_x from the NO_x absorbent 22 by making the air-fuel ratio of the exhaust gas rich for a short time of less than one second, but releasing all of the SO_x from the NO_x absorbent 22 requires the temperature of the NO_x absorbent 22 to be maintained at not less than about 600°C and the air-fuel ratio of the exhaust gas to be maintained at the stoichiometric air-fuel ratio or rich for about 10 minutes. That is, in order to make all of the SO_x be released from the NO_x absorbent 22, it is necessary to first raise the temperature of the NO_x absorbent 22 to over 600°C and then keep the air-fuel ratio of the exhaust gas at the stoichiometric air-fuel ratio or rich and maintain the NO_x absorbent 22 at a high temperature.

[0026] Since releasing the SO_x from the NO_x absorbent 22 in this way requires first that the temperature of the NO_x absorbent 22 be raised, it is preferable to raise the temperature of the NO_x absorbent 22 as fast as possible. If the temperature of the NO_x absorbent 22 is made to rise too quickly, however, the problem arises of the temperature of the NO_x absorbent 22 rising to an extreme degree and there being the risk of thermal deterioration of the NO_x absorbent 22. That is, there is an optimal required value for the temperature raising rate of the NO_x absorbent 22 and it is necessary to raise the temperature of the NO_x absorbent in accordance with that required value. The required value will be explained in detail later. Before that, the method of raising the temperature of the NO_x absorbent 22 will be explained.

[0027] In the present invention, to raise the temperature of the NO_x absorbent 22, use is made of a combination of two methods: the method of raising the temperature of the exhaust gas and the method of increasing the amount of unburned hydrocarbons in the exhaust gas. In this case, in the present invention, the injection timing of the main fuel is delayed so as to raise the temperature of the exhaust gas and auxiliary fuel is injected in addition to the main fuel so as to increase the amount of the unburned hydrocarbons in the exhaust gas. Various injection patterns different in at least one of the amount of retardation of the injection timing of the main fuel and the injection timing of the auxiliary fuel are used.

[0028] That is, in this embodiment of the present invention, roughly classified, four injection patterns are used, that is, a first pattern of delaying the injection timing of the main fuel without injecting auxiliary fuel, a second pattern of injecting auxiliary fuel before injecting the main fuel and delaying the injection timing of the main fuel, a third pattern of injecting auxiliary fuel before injecting the main fuel and after injecting the main fuel and

delaying the injection timing of the main fuel, and a fourth pattern of injecting auxiliary fuel after injecting the main fuel and delaying the injection timing of the main fuel.

[0029] Next, an explanation will be given of these four injection patterns with reference to Fig. 8 to Fig. 11. Figure 8 to Fig. 10 show the injection timings of the main fuel and the injection timings of the auxiliary fuel. The abscissas show the crank angle. Further, Fig. 8 to Fig. 10 show the opening timings of the intake valve 7, the opening timings of the exhaust valve 9, and the injection timing X in which fuel injected from a fuel injector 6 can be supplied into a cavity 5a (Fig. 1) formed at the top face of the piston 4. On the other hand, Fig. 11 shows the injection start timing θ_S of the main fuel. The abscissa in Fig. 11 shows the required torque TQ.

[0030] In Fig. 8 to Fig. 10, (I) shows the injection timing at the time of ordinary operation. As will be understood from Fig. 8, Fig. 9, and Fig. 10, auxiliary fuel is not injected during ordinary operation. Only main fuel Q is injected. The injection start timing θ_S of the main fuel Q at this time is shown by I in Fig. 11. As will be understood from Fig. 11, the injection start timing θ_S of the main fuel at this time is made before top dead center of the compression stroke.

[0031] On the other hand, (II) shows the first injection pattern. As explained above, in the first injection pattern, only the main fuel Q_R is injected, without injection of the auxiliary fuel. Further, at this time, the injection timing of the main fuel Q_R is delayed compared with the time of ordinary operation. II in Fig. 11 shows the injection start timing θ_S of the main fuel Q_R at this time. As shown in Fig. 11, the injection start timing θ_S of the main fuel Q_R at this time is delayed until after top dead center of the compression stroke and is delayed more the higher the required torque TQ.

[0032] Once past top dead center of the compression stroke, the pressure in the combustion chamber 5 gradually falls and the temperature in the combustion chamber 5 also gradually falls. Since the pressure in the combustion chamber 5 gradually falls after the top dead center of the compression stroke in this way, if the injection start timing θ_S of the main fuel Q_R is delayed until after top dead center of the compression stroke, the injected fuel will be made to widely diffuse inside the combustion chamber 5 and will be ignited after being widely diffused. That is, the fuel will be burned in a state with sufficient air present around it. As a result, soot will not be produced much. Further, at the time of ignition, the pressure and temperature in the combustion chamber 5 become low, therefore the combustion temperature will not rise that much. Accordingly, not that much NO_x will be produced either.

[0033] On the other hand, if the injection start timing θ_S of the main fuel Q_R is delayed in this way, the combustion time will become longer and therefore the temperature of the exhaust gas will rise. If the temperature of the exhaust gas rises, the temperature of the exhaust

gas after-treatment device 21, in the embodiment shown in Fig. 1, the temperature of the NO_x absorbent 22, will be made to rise. In this case, the more the injection start timing θ_S of the main fuel Q_R is delayed, the higher the temperature of the exhaust gas and therefore, from the viewpoint of raising the temperature of the NO_x absorbent 22, it is preferable to delay the injection start timing θ_S of the main fuel Q_R as much as possible. If the injection start timing θ_S of the main fuel Q_R is delayed too much, however, misfires will occur. Therefore, in the first injection pattern, the injection start timing θ_S of the main fuel Q_R is set to a timing as much delayed as possible while still in a range where no misfires occur.

[0034] (III) in Fig. 8 shows a first example of the second injection pattern. In this example, auxiliary fuel Q_v is injected near top dead center of the suction stroke. Compared with the case of the first injection pattern shown by (II) in Fig. 8, the injection start timing θ_S of the main fuel Q_R is further delayed. The III of Fig. 11 shows the injection start timing θ_S of the main fuel at this time. As shown in Fig. 11, the injection start timing θ_S of the main fuel Q_R at this time is delayed further from the case of the first injection pattern shown by (II) in Fig. 11. Further, at this time as well, the injection start timing θ_S of the main fuel Q_R is delayed more the higher the required torque TQ.

[0035] In the vicinity of the top dead center of the suction stroke, almost no suction air has been fed into the combustion chamber 5 and, thus, the unburned gas is maintained at a high temperature. Accordingly, if the auxiliary fuel Q_v is injected rear top dead center of the suction stroke, the auxiliary fuel Q_v is instantaneously vaporized. If the auxiliary fuel Q_v is vaporized, the heat of compression during the compression stroke causes the production of aldehydes, ketones, peroxides, carbon monoxide, and other intermediate products from the auxiliary fuel Q_v . These intermediate products cause the reaction of the main fuel Q_R to be accelerated. Therefore, in this case, even if the injection start timing θ_S of the main fuel Q_R is delayed by a large extent, good combustion can be obtained without causing misfires. On the other hand, since the injection start timing θ_S of the main fuel Q_R can be delayed by a large extent in this way, the temperature of the exhaust gas becomes considerably high and therefore the temperature of the NO_x absorbent 22 can be raised to a higher level.

[0036] Further, in the example shown by (III) in Fig. 8, when the exhaust valve 9 opens, auxiliary fuel Q_v is injected, so part of the auxiliary fuel Q_v is exhausted into the exhaust port 10 in the form of unburned hydrocarbons. The unburned hydrocarbons, if reaching the NO_x absorbent 22, are oxidized by the excess oxygen in the exhaust gas. The heat of the oxidation reaction occurring at this time causes the temperature of the NO_x absorbent 22 to rise rapidly to a further higher level. That is, in this example, the dual actions of the action of raising the temperature of the exhaust gas and the action of increasing the unburned hydrocarbons in the exhaust

gas result in the temperature of the NO_x absorbent 22 being raised.

[0037] Further, in the example shown by (III) in Fig. 8, auxiliary fuel Q_v is injected at the injection timing X where the injected fuel is supplied into the cavity 5a of the piston 4. Therefore, it is possible to prevent the auxiliary fuel Q_v from depositing on the inner wall of the cylinder bore. As a result, it is possible to prevent the lubrication oil from being diluted by the injected fuel.

[0038] (III) in Fig. 9 shows a second example of the second injection pattern. In this second example, the auxiliary fuel Q_e is injected at the end of the compression stroke. Compared with the case of the first pattern shown by (II) in Fig. 9, the injection start timing θ_S of the main fuel Q_R is further delayed. The injection start timing θ_S of the main fuel Q_R at this time is shown by III in Fig. 11. In this case as well, aldehydes, ketones, peroxides, carbon monoxide, and other intermediate products are produced from the auxiliary fuel Q_e and these intermediate products cause the reaction of the main fuel Q_R to be accelerated. Therefore, in this case as well, even if the injection start timing θ_S of the main fuel Q_R is delayed by a large extent, good combustion can be secured without causing misfires.

[0039] In the second example as well, since the auxiliary fuel Q_e is injected at the injection timing X where the injected fuel is supplied into the cavity 5a of the piston 4, it is possible to prevent the auxiliary fuel Q_e from depositing on the inner wall of the cylinder bore.

[0040] Note that in the second example, unlike the first example shown by (III) in Fig. 8, fuel is not injected to positively increase the amount of unburned hydrocarbons in the exhaust gas. That is, the second example is aimed at raising the temperature of the exhaust gas by delaying the injection start timing θ_S of the main fuel Q_R further from the case of the first injection pattern shown by (II) in Fig. 9. Therefore, compared with the case of the first injection pattern shown by (II) in Fig. 9, the second example has a more powerful action of raising the temperature of the NO_x absorbent 22, but compared with the first example, the second example has a weaker action of raising the temperature of the NO_x absorbent 22.

[0041] (IV-1) and (IV-2) in Fig. 8 show a first example of the third injection pattern. In the first example, the auxiliary fuel Q_v and main fuel Q_R are injected at the same timings as the second injection pattern shown by (III) in Fig. 8 and auxiliary fuel Q_p is further injected during the expansion stroke or exhaust stroke after injection of the main fuel Q_R . In the example shown in Fig. 8, the auxiliary fuel Q_p is injected during the expansion stroke just before the exhaust valve 9 opens.

[0042] The auxiliary fuel Q_p is not burned in the combustion chamber 5, therefore if the auxiliary fuel Q_p is injected, the auxiliary fuel Q_p is exhausted into the exhaust port 10 in the form of unburned hydrocarbons. Therefore, if the auxiliary fuel Q_p is injected, the amount of unburned hydrocarbons in the exhaust gas is in-

creased and therefore the heat of oxidation reaction of the unburned hydrocarbons causes the temperature of the NO_x absorbent 22 to rapidly rise. Compared with the case of making the temperature of the exhaust gas rise to raise the temperature of the NO_x absorbent 22, increasing the amount of unburned hydrocarbons in the exhaust gas and using the heat of oxidation reaction to raise the temperature of the NO_x absorbent 22 enables the temperature of the NO_x absorbent 22 to be raised far more rapidly, so compared with the case of using the second injection pattern shown by (III) in Fig. 8, use of the third injection pattern shown by (IV-1) and (IV-2) in Fig. 8 enables the temperature of the NO_x absorbent 22 to be raised far more rapidly. The auxiliary fuel Q_p , however, does not contribute to the production of output in the engine, so if the auxiliary fuel Q_p is injected, the amount of fuel consumption is increased.

[0043] When making the temperature of the NO_x absorbent 22 rise more rapidly, as shown by (IV-2) in Fig. 8, the number of injections of the auxiliary fuel Q_p may be increased. That is, if injecting a large amount of auxiliary fuel Q_p , the penetration force of the injected fuel becomes greater, so part of the auxiliary fuel Q_p ends up depositing on the inner wall of the cylinder bore. As opposed to this, if the amount of injection of the auxiliary fuel Q_p is reduced, the penetration force of the injected fuel becomes smaller, so the auxiliary fuel Q_p will no longer deposit on the inner wall of the cylinder bore. Therefore, when increasing the amount of injection of the auxiliary fuel Q_p , as shown by (IV-2) in Fig. 8, small amounts of the auxiliary fuel Q_p are injected at intervals over several times.

[0044] (IV-1) and (IV-2) of Fig. 8 show a second example of the third injection pattern. In the second example, the auxiliary fuel Q_e and the main fuel Q_R are injected at the same timings as the second injection pattern shown by (III) in Fig. 9 and further auxiliary fuel Q_p is injected during the expansion stroke or exhaust stroke after the injection of the main fuel Q_R . In the example shown in Fig. 9, the auxiliary fuel Q_p is injected during the expansion stroke right before the exhaust valve 9 opens.

[0045] In the second example as well, when making the temperature of the NO_x absorbent 22 rise more rapidly, as shown by (IV-2) in Fig. 9, the number of injections of the auxiliary fuel Q_p may be increased.

[0046] (III-1), (III-2), and (III-3) of Fig. 10 show the fourth injection pattern. In this fourth injection pattern, the main fuel Q_R is injected at the same timing as the first injection pattern shown by (II) of Fig. 10 and further auxiliary fuel Q_p is injected during the expansion stroke or exhaust stroke after injection of the main fuel Q_R . In the example shown in Fig. 10, the auxiliary fuel Q_p is injected during the expansion stroke right before the exhaust valve 9 opens.

[0047] In the fourth injection pattern as well, when making the temperature of the NO_x absorbent 22 rise more rapidly, as shown by (III-2) and (III-3) in Fig. 10,

the number of injections of the auxiliary fuel Q_P may be increased.

[0048] If the injection pattern is changed in this way, one or both of the temperature of the exhaust gas or the amount of the unburned hydrocarbons in the exhaust gas change, therefore the rate of rise of the temperature of the NO_x absorbent 22 changes. Further, even with the same injection pattern, if the number of injections of the auxiliary fuel Q_P after top dead center of the compression stroke is changed, the amount of unburned hydrocarbons in the exhaust gas changes and therefore the rate of rise of the temperature of the NO_x absorbent 22 changes. Accordingly, by changing the injection pattern or changing the number of injections of the auxiliary fuel Q_P after top dead center of the compression stroke, it is possible to control the temperature raising rate of the NO_x absorbent 22 to the optimal rate.

[0049] Next, as one example, an explanation will be given of the case of using the first injection pattern shown by (II) in Fig. 8, the second injection pattern shown by (III) in Fig. 8, and the third injection pattern shown by (IV-1) and (IV-2) in Fig. 8 when raising the temperature of the NO_x absorbent 22 to the target temperature, for example, 650°C.

[0050] Figure 12 shows the relationship between the injection pattern used when raising the temperature of the NO_x absorbent 22, the required torque TQ , and the engine rotational speed N . That is, the region shown by Q in Fig. 12 shows the operating region where the injection Q of ordinary operation shown by (I) in Fig. 8 is performed, the region shown by Q_R shows the operating region where injection is performed by the first injection pattern Q_R shown by (II) in Fig. 8, the region shown by Q_V+Q_R shows the operating region where injection is performed by the second injection pattern Q_V+Q_R shown by (III) in Fig. 8, and the region shown by $Q_V+Q_R+Q_P$ shows the operating region where injection is performed by the third injection pattern $Q_V+Q_R+Q_P$ shown by (IV-1) or (IV-2) in Fig. 8.

[0051] Further, (1) in Fig. 12 shows when the temperature TC of the exhaust gas after-treatment device 21, in this embodiment, the temperature TC of the NO_x absorbent 22, is lower than a predetermined first temperature $T1$, for example 300°C, (2) in Fig. 12 shows when the temperature TC of the NO_x absorbent 22 is higher than the first temperature $T1$ and lower than a predetermined second temperature $T2$, for example, 500°C, and (3) in Fig. 12 shows when the temperature TC of the NO_x absorbent 22 is higher than the second temperature $T2$.

[0052] When the temperature TC of the NO_x absorbent 22 is lower than the first temperature $T1$, as shown by (1) in Fig. 12, injection is performed by the second injection pattern Q_V+Q_R in only the limited operating region where the required torque TQ is high and the engine rotational speed N is high, while injection is performed by the third injection pattern $Q_V+Q_R+Q_P$ in the greater portion of the other operating region.

[0053] On the other hand, when the temperature TC of the NO_x absorbent 22 is $T1 \leq TC < T2$, as shown by (2) in Fig. 12, injection is performed by the first injection pattern Q_R in the limited operating region where the required torque TQ is high and the engine rotational speed N is high, injection is performed by the second injection pattern Q_V+Q_R in the operating region at the low load side of this operating region, and injection is performed by the third injection pattern $Q_V+Q_R+Q_P$ in the operating region at the further lower load side of this operating region.

[0054] On the other hand, when the temperature TC of the NO_x absorbent 22 is $T2 \leq TC$, as shown by (3) in Fig. 12, injection of an ordinary operation is performed in the limited operating region where the required torque TQ is high and the engine rotational speed N is high, injection is performed by the first injection pattern Q_R in the operating region at the low load side of this operating region, injection is performed by the second injection pattern Q_V+Q_R in the operating region at the further lower load side of this operating region, and injection is performed by the third injection pattern $Q_V+Q_R+Q_P$ in the operating region at the further lower load side of this operating region.

[0055] That is, as the temperature TC of the NO_x absorbent 22 becomes higher, the operating region where injection is performed by the first injection pattern Q_R and the operating region where injection is performed by the second injection pattern Q_V+Q_R shift to the low load side.

[0056] Figure 13A shows the change in the temperature TC of the NO_x absorbent 22 and the change in the injection pattern when assuming the action of raising the temperature of the NO_x absorbent 22 is started and the same required torque TQ and engine rotational speed N are maintained after that as well in the case of the required torque TQ and the engine rotational speed N shown by the point A in Fig. 12. Note that the solid line (1) in Fig. 13A, shows the case where the action of raising the temperature of the NO_x absorbent 22 was started when $TC < T1$ as shown by (1) in Fig. 12, the solid line (2) in Fig. 13A shows the case where the action of raising the temperature of the NO_x absorbent 22 was started when $T1 \leq TC < T2$ as shown by (2) in Fig. 12, and the solid line (3) in Fig. 13A shows the case where the action of raising the temperature of the NO_x absorbent 22 was started when $T2 \leq TC$ as shown by (3) in Fig. 12.

[0057] Further, in Fig. 13A, the action of raising the temperature of the NO_x absorbent 22 is started when an SO_x releasing flag showing that SO_x should be released from the NO_x absorbent 22 is set. The action of releasing the SO_x from the NO_x absorbent 22 is started when the temperature TC of the NO_x absorbent 22 passes a target temperature T_{max} where the SO_x can be released.

[0058] If the action of raising the temperature of the NO_x absorbent 22 is started when $TC < T1$, first injection is performed by the third injection pattern $Q_V+Q_R+Q_P$,

then when $TC \geq T_1$, injection is performed by the second injection pattern $Q_V + Q_R$, then, when $TC \geq T_2$, injection is performed by the first injection pattern Q_R . In this case, the temperature raising rate of the NO_x absorbent 22 due to the third injection pattern $Q_V + Q_R + Q_P$ is the highest, the temperature raising rate of the NO_x absorbent 22 due to the second injection pattern $Q_V + Q_R$ is the next highest, and the temperature raising rate of the NO_x absorbent 22 due to the first injection pattern Q_R is the lowest.

[0059] Therefore, if the action of raising the temperature of the NO_x absorbent 22 is started when $TC < T_1$, as shown by the solid line (1) of Fig. 13A, the temperature TC of the NO_x absorbent 22 rapidly rises, then, when the temperature TC of the NO_x absorbent 22 passes T_1 , the temperature raising rate of the NO_x absorbent 22 falls a bit, then, when the temperature TC of the NO_x absorbent 22 passes T_2 , the temperature raising rate of the NO_x absorbent 22 becomes further lower.

[0060] On the other hand, if the action of raising the temperature of the NO_x absorbent 22 is started when $T_1 \leq TC < T_2$, first, injection is performed by the second injection pattern $Q_V + Q_R$, then, when $TC \geq T_2$, injection is performed by the first injection pattern Q_R . Therefore, at this time, as shown by the solid line (2) in Fig. 13A, first the temperature TC of the NO_x absorbent 22 rises relatively slowly, then, when the temperature TC of the NO_x absorbent 22 passes T_2 , the temperature raising rate of the NO_x absorbent 22 becomes lower.

[0061] On the other hand, if the action of raising the temperature of the NO_x absorbent 22 is started when $T_2 \leq TC$, injection is performed by the first injection pattern Q_R , therefore, at this time, as shown by the solid line (3) in Fig. 13A, the temperature TC of the NO_x absorbent 22 slowly rises.

[0062] Figure 13B shows the change in the temperature TC of the NO_x absorbent 22 and the change in the injection pattern when assuming the action of raising the temperature of the NO_x absorbent 22 is started and the same required torque TQ and engine rotational speed N are maintained after that as well in the case of the required torque TQ and the engine rotational speed N shown by the point B in Fig. 12. Note that the solid line (1) in Fig. 13B shows the case where the action of raising the temperature of the NO_x absorbent 22 was started when $TC < T_1$ as shown by (1) in Fig. 12, the solid line (2) in Fig. 13B shows the case where the action of raising the temperature of the NO_x absorbent 22 was started when $T_1 \leq TC < T_2$ as shown by (2) in Fig. 12, and the solid line (3) in Fig. 13B shows the case where the action of raising the temperature of the NO_x absorbent 22 was started when $T_2 \leq TC$ as shown by (3) in Fig. 12.

[0063] When maintaining the required torque TQ and the engine rotational speed N shown by the point B in Fig. 12, as will be understood from Fig. 12, whether $TC < T_1$, $T_1 \leq TC < T_2$, or $T_2 \leq TC$, injection is performed by the third injection pattern $Q_V + Q_R + Q_P$, therefore as shown by the solid lines (1), (2), and (3) in Fig. 13B, the

temperature raising rate of the NO_x absorbent 22 becomes about the same regardless of the temperature TC of the NO_x absorbent 22.

[0064] That is, as shown by the solid line (1) of Fig. 13A, if the action of raising the temperature of the NO_x absorbent 22 is started when $TC < T_1$, that is, if the action of raising the temperature of the NO_x absorbent 22 is started when there is a large difference between the temperature TC of the NO_x absorbent 22 and the target temperature T_{max} , injection is performed by the third injection pattern $Q_V + Q_R + Q_P$ so as to raise the temperature TC of the NO_x absorbent 22 to the target temperature T_{max} as fast as possible. When performing injection by this third injection pattern $Q_V + Q_R + Q_P$, however, the temperature TC of the NO_x absorbent 22 will rapidly rise, so it will be difficult to control the temperature TC of the NO_x absorbent 22 and consequently if just this third injection pattern $Q_V + Q_R + Q_P$ is used, the temperature TC of the NO_x absorbent 22 will end up greatly exceeding the target temperature T_{max} and therefore there will be the risk of thermal deterioration of the NO_x absorbent 22. Further, if the third injection pattern $Q_V + Q_R + Q_P$ continues to be used, the amount of fuel consumption will increase.

[0065] Therefore, when $TC \geq T_1$, in order to prevent thermal deterioration of the NO_x absorbent 22 and reduce the amount of fuel consumption, the third injection pattern $Q_V + Q_R + Q_P$ is switched to the second injection pattern $Q_V + Q_R$, then, when the temperature TC of the NO_x absorbent 22 approaches the target temperature T_{max} , that is, when $TC \geq T_2$, the second injection pattern $Q_V + Q_R$ is switched to the first injection pattern Q_R . If the first injection pattern Q_R is used, the temperature raising rate of the NO_x absorbent 22 becomes smaller and therefore the control of the temperature TC of the NO_x absorbent 22 becomes easy. Accordingly, it is possible to prevent thermal deterioration of the NO_x absorbent 22 and possible to reduce the amount of fuel consumption.

[0066] Further, in the case shown by the solid line (2) in Fig. 13A, the temperature TC of the NO_x absorbent 22 is first made to rise relatively quickly, then to prevent thermal deterioration of the NO_x absorbent 22 and reduce the amount of fuel consumption, the second injection pattern $Q_V + Q_R$ is switched to the first injection pattern Q_R . Further, as shown by the solid line (3) in Fig. 13A, when the action of raising the temperature of the NO_x absorbent 22 is started when $TC \geq T_2$, injection is performed by the first injection pattern Q_R from the start so as to prevent thermal deterioration of the NO_x absorbent 22 and reduce the amount of fuel consumption.

[0067] On the other hand, when the required torque TQ is low as shown by the point B in Fig. 12, the amount of fuel injection is small and therefore even if the injection timing of the main fuel is delayed, the temperature of the exhaust gas will not become that high. Therefore, at this time, to make the temperature of the NO_x absorbent 22 rise as fast as possible, injection is performed by

the third injection pattern $Q_V+Q_R+Q_P$ regardless of the temperature TC of the NO_x absorbent 22. When the temperature of the exhaust gas is not that high in this way, however, even if injection is performed by the third injection pattern $Q_V+Q_R+Q_P$, as shown by the solid lines (1), (2), and (3) of Fig. 13B, the temperature raising rate of the NO_x absorbent 22 will not become that high. Therefore, at this time, even if injection is performed by the third injection pattern $Q_V+Q_R+Q_P$, the temperature TC of the NO_x absorbent 22 can be easily controlled and consequently there is no risk of the temperature TC of the NO_x absorbent 22 become extremely high and of thermal deterioration of the NO_x absorbent 22.

[0068] In this way, in this embodiment of the present invention, when raising the temperature TC of the NO_x absorbent 22, the optimal injection pattern for the temperature TC of the NO_x absorbent 22, the required torque TQ, and the engine rotational speed N is used. Note that the injection patterns shown in Fig. 12 are just examples and it is possible to use a fourth injection pattern Q_R+Q_P in accordance with need.

[0069] In Fig. 13A and 13B, when the temperature TC of the NO_x absorbent 22 exceed a target temperature T_{\max} of 600°C to 700°C, control is performed to release the SO_x from the NO_x absorbent 22. Next, an explanation will be given of the control for release of the SO_x with reference to Fig. 14.

[0070] Figure 14 shows the degree of opening ST of the throttle valve 17, the degree of opening SE of the EGR control valve 25, the air-fuel ratio of the combustion gas of the main fuel in the combustion chamber 5, the EGR rate, and the injection start timing θ_S of the main fuel when releasing SO_x from the NO_x absorbent 22. Note that in the degree of opening ST of the throttle valve 17 and the degree of opening SE of the EGR control valve 25 of Fig. 14, the dash-dot lines show the degrees of opening at the time of ordinary operation shown in Fig. 3 and the solid lines shown the degrees of opening at the time of release of SO_x . Further, in the air-fuel ratio of the combustion gas, the broken line shows the limit of production of smoke. Smoke is produced in the hatched region. Further, in the injection start timing θ_S of the main fuel, the broken line shows the timing at the time of ordinary operation and the solid line shows the timing at the time of release of SO_x .

[0071] As shown in Fig. 14, when SO_x is to be released from the NO_x absorbent 22, the EGR control valve 25 is completely closed, therefore the EGR rate becomes zero. Further, the injection start timing θ_S of the main fuel is delayed to after the top dead center of the compression stroke. At this time, the degree of opening ST of the throttle valve 17 is reduced so that the air-fuel ratio of the combustion gas of the main fuel becomes the target air-fuel ratio shown by the solid line slightly larger than the smoke limit. The target air-fuel ratio of the combustion gas shown by the solid line becomes smaller the lower the required torque TQ, therefore the degree of opening ST of the throttle valve 17

becomes smaller the lower the required torque TQ.

[0072] Further, when SO_x is to be released from the NO_x absorbent 22, the auxiliary fuel Q_P is injected during the expansion stroke or exhaust stroke so that the air-fuel ratio of the exhaust gas flowing into the NO_x absorbent 22 becomes the stoichiometric air-fuel ratio or rich. In this embodiment of the present invention, auxiliary fuel Q_P is injected during the expansion stroke right before the exhaust valve 9 opens so that the exhaust gas flowing into the NO_x absorbent 22 becomes just slightly rich. That is, when SO_x is to be released from the NO_x absorbent 22, injection is performed by the fourth injection pattern Q_R+Q_P shown by (III-1) or (III-2) or (III-3) of Fig. 10. As shown in Fig. 15, when SO_x is to be released from the NO_x absorbent 22, the amount of the auxiliary fuel Q_P increases the higher the required torque TQ.

[0073] The degree of opening ST of the throttle valve 17 and the injection start timing θ_S of the main fuel when SO_x is to be released from the NO_x absorbent 22 are not functions of just the required torque TQ, but are functions of the required torque TQ and the engine rotational speed N. In this embodiment of the present invention, the degree of opening ST of the throttle valve 17 and the injection start timing θ_S of the main fuel when SO_x is to be released from the NO_x absorbent 22 are stored in advance in the ROM 32 in the form of maps as functions of the required torque TQ and the engine rotational speed N as shown in Fig. 16A and Fig. 16B.

[0074] Figure 17 shows another embodiment of the control for release of SO_x from the NO_x absorbent 22. In this embodiment, when the required torque TQ becomes less than a certain torque, the degree of opening ST of the throttle valve 17 is made a fixed degree of opening and the degree of opening SE of the EGR control valve 25 is made larger as the required torque TQ becomes lower.

[0075] On the other hand, when NO_x is to be released from the NO_x absorbent 22, there is no particular need to raise the temperature of the NO_x absorbent 22. At this time, it is sufficient to make the air-fuel ratio of the exhaust gas flowing into the NO_x absorbent 22 temporarily rich.

[0076] Figure 18 shows the degree of opening ST of the throttle valve 17, the degree of opening SE of the EGR control valve 25, the air-fuel ratio of the combustion gas of the main fuel in the combustion chamber 5, the EGR rate, and the injection start timing θ_S of the main fuel when NO_x is to be released from the NO_x absorbent 22. Note that in the degree of opening ST of the throttle valve 17 and the degree of opening SE of the EGR control valve 25 in Fig. 18, the chain lines show the degrees of opening at the time of ordinary operation shown in Fig. 3 and the dash-dot lines show the degrees of opening at the time of release of NO_x . Further, in the air-fuel ratio of the combustion gas, the broken line shows the limit of production of smoke. Smoke is produced in the hatched region. Further, in the injection start timing θ_S of the main fuel, the broken line shows the timing at the

time of ordinary operation while the solid line shows the timing at the time of release of NO_x .

[0077] As shown in Fig. 18, when NO_x is to be released from the NO_x absorbent 22, the EGR control valve 25 is completely closed and therefore the EGR rate becomes zero. Further, the injection start timing θ_S of the main fuel is delayed to after the top dead center of the compression stroke. At this time, the degree of opening ST of the throttle valve 17 is reduced so that the air-fuel ratio of the combustion gas of the main fuel becomes the target air-fuel ratio shown by the solid line slightly larger than the smoke limit. The degree of opening ST of the throttle valve 17 and the injection start timing θ_S of the main fuel shown in Fig. 18 are the same as the degree of opening ST of the throttle valve and the injection start timing θ_S of the main fuel at the time of release of SO_x shown in Fig. 14. Therefore, the degree of opening ST of the throttle valve 17 and the injection start timing θ_S of the main fuel at the time of release of NO_x are calculated from the maps shown by Fig. 16A and Fig. 16B.

[0078] Further, when NO_x is to be released from the NO_x absorbent 22, auxiliary fuel Q_P is injected during the expansion stroke or exhaust stroke so that the air-fuel ratio of the exhaust gas flowing into the NO_x absorbent 22 becomes rich. In this embodiment of the present invention, auxiliary fuel Q_P is injected during the expansion stroke immediately before the exhaust valve 9 opens so that the exhaust gas flowing into the NO_x absorbent 22 becomes rich. That is, when NO_x is to be released from the NO_x absorbent 22, injection is performed by the fourth injection pattern Q_R+Q_P shown by (III-1), (III-2), or (III-3) in Fig. 10. As shown in Fig. 19, the amount of auxiliary fuel Q_P when SO_x is to be released from the NO_x absorbent 22 increases the higher the required torque TQ.

[0079] Next, an explanation will be made of the processing routine for the NO_x releasing flag which is set when NO_x is to be released from the NO_x absorbent 22 and the SO_x releasing flag which is set when SO_x is to be released from the NO_x absorbent 22 while referring to Fig. 20. Note that this routine is executed by interruption every predetermined time interval.

[0080] Referring to Fig. 20, first, at step 100, the amount AX of absorption of NO_x per unit time is calculated from the map shown in Fig. 7. Next, at step 101, AX is added to the amount ΣNOX of absorption of NO_x . Next, at step 102, it is determined if the amount ΣNOX of absorption of NO_x has exceeded a maximum allowable value MAX1. If $\Sigma\text{NOX} > \text{MAX1}$, the routine proceeds to step 103, where the NO_x releasing flag showing that NO_x should be released is set. Next, the routine proceeds to step 104.

[0081] At step 104, the product $k \cdot Q$ obtained by multiplication of a constant k with the amount of injection Q is added to ΣSOX . The fuel contains a substantially fixed amount of sulfur S, therefore the amount of SO_x absorbed in the NO_x absorbent 22 can be expressed by

$k \cdot Q$. Therefore, the ΣSOX obtained by successively adding this $k \cdot Q$ shows the amount of SO_x estimated to be absorbed in the NO_x absorbent 22. At step 105, it is determined if this amount ΣSOX of SO_x has exceeded a maximum allowable value MAX2. When $\Sigma\text{SOX} > \text{MAX2}$, the routine proceeds to step 106, where the SO_x releasing flag is set.

[0082] Next, an explanation will be made of the operational control with reference to Fig. 21.

[0083] Referring to Fig. 21, first, at step 200, it is determined if the SO_x releasing flag has been set. When the SO_x releasing flag has not been set, the routine proceeds to step 201, where it is determined if the NO_x releasing flag has been set. When the NO_x releasing flag has not been set, the routine proceeds to step 202, where ordinary operation is performed.

[0084] That is, at step 202, the target degree of opening ST of the throttle valve 17 is calculated from the map shown in Fig. 5A and the degree of opening of the throttle valve 17 is made this target degree of opening ST. Next, at step 203, the target degree of opening SE of the EGR control valve 25 is calculated from the map shown in Fig. 5B and the degree of opening of the EGR control valve 25 is made this target degree of opening SE. Next, at step 204, the amount of injection Q is calculated from the map shown in Fig. 4A and the injection start timing θ_S is calculated from the map shown in Fig. 4B. The fuel is injected on the basis of these calculated values.

[0085] On the other hand, when it is determined at step 201 that the NO_x releasing flag has been set, the routine proceeds to step 205, where NO_x release processing for release of NO_x from the NO_x absorbent 22 is performed. That is, at step 205, the target degree of opening ST of the throttle valve 17 is calculated from the map shown in Fig. 16A and the degree of opening of the throttle valve 17 is made this target degree of opening ST. At this time, the EGR control valve 25 is completely closed. Next, at step 206, the injection start timing θ_S of the main fuel is calculated from the map shown in Fig. 16B. Next, at step 207, the main fuel is injected at the injection start timing θ_S calculated at step 206, then the auxiliary fuel Q_P is injected during the expansion stroke.

[0086] That is, at this time, the degree of opening of the throttle valve 17 is reduced, injection is performed by the fourth injection pattern shown in Fig. 10, and thereby the air-fuel ratio of the exhaust gas flowing into the NO_x absorbent 22 is made rich. Next, at step 208, it is determined if a fixed time has elapsed from when the air-fuel ratio of the exhaust gas was made rich. When a fixed time has elapsed, the routine proceeds to step 209, where the NO_x releasing flag is reset. At this time, simultaneously, ΣNOX (Fig. 20) is made zero.

[0087] On the other hand, when it is judged at step 200 that the SO_x releasing flag has been set, the routine proceeds to step 210, where it is determined if a temperature raising completion flag showing that the NO_x

absorbent 22 has been raised to a temperature enabling release of SO_x has been set. When the SO_x releasing flag has been set, the temperature raising completion flag is reset, therefore the routine proceeds to step 300 where control is performed for raising the temperature. This control for raising the temperature is shown in Fig. 22.

[0088] Referring to Fig. 22, first, at step 301, the target degree of opening ST of the throttle valve 17 is calculated from the map shown in Fig. 5A and the degree of opening of the throttle valve 17 is made this target degree of opening ST. Next, at step 302, the target degree of opening SE of the EGR control valve 25 is calculated from the map shown in Fig. 5B and the degree of opening of the EGR control valve 25 is made this target degree of opening SE. Next, at step 303, it is determined if the temperature TC of the NO_x absorbent 22 detected by the temperature sensor 39 is lower than a first temperature T_1 . When $\text{TC} < T_1$, the routine proceeds to step 304, where injection is performed by the injection pattern determined based on (1) of Fig. 12.

[0089] On the other hand, when it is judged at step 303 that $\text{TC} \geq T_1$, the routine proceeds to step 305, where it is determined if the temperature TC of the NO_x absorbent 22 detected by the temperature sensor 39 is lower than a second temperature T_2 . When $\text{TC} < T_2$, the routine proceeds to step 306, where injection is performed by an injection pattern determined based on (2) of Fig. 12.

[0090] On the other hand, when it is determined at step 305 that $\text{TC} \geq T_2$, the routine proceeds to step 307, where injection is performed by the injection pattern determined based on (3) of Fig. 12. Next, at step 308, it is determined if the temperature TC of the NO_x absorbent 22 detected by the temperature sensor 39 has become higher than the target temperature T_{max} . When $\text{TC} \geq T_{\text{max}}$, the routine proceeds to step 309, where the temperature raising completion flag is set.

[0091] Returning again to Fig. 21, when the temperature raising completion flag is set, the routine proceeds to step 211, where SO_x release processing is performed for releasing the SO_x from the NO_x absorbent 22. That is, at step 211, the target degree of opening ST of the throttle valve 17 is calculated from the map shown in Fig. 16A and the degree of opening of the throttle valve 17 is made this target degree of opening ST. At this time, the EGR control valve 25 is completely closed. Next, at step 212, the injection start timing θ_S of the main fuel is calculated from the map shown in Fig. 16B. Next, at step 213, the main fuel is injected at the injection start timing θ_S calculated at step 212, then auxiliary fuel Q_p is injected during the expansion stroke.

[0092] That is, at this time, the degree of opening of the throttle valve 17 is reduced and injection is performed by the fourth injection pattern shown in Fig. 10, whereby the air-fuel ratio of the exhaust gas flowing into the NO_x absorbent 22 is made just slightly rich. Next, at step 214, it is determined if a fixed time has elapsed

from when the air-fuel ratio of the exhaust gas was made just slightly rich. When the fixed time has elapsed, the routine proceeds to step 216, where the NO_x releasing flag, the SO_x releasing flag, and the temperature raising completion flag are reset. At this time, simultaneously, ΣNOX and ΣSOX (Fig. 20) are made zero.

[0093] Figure 23 shows another embodiment. In this embodiment, the exhaust gas after-treatment device 21 is comprised of a particulate filter 50 for trapping particulate matter in the exhaust gas and a casing 51 housing this particulate filter 50. Further, in this embodiment, a differential pressure sensor 52 is provided for detecting the differential pressure before and after the particulate filter 50.

[0094] The particulate matter deposited on the particulate filter 50 naturally ignites when the temperature of the particulate filter 50 passes a fixed temperature T_0 . If it were possible to maintain the temperature of the particulate filter 50 after that to at least that fixed temperature T_0 , then it would be possible to burn all of the particulate matter deposited on the particulate filter 50. That is, to burn all of the particulate matter deposited on the particulate filter 50, that is, when regenerating the particulate filter 50, it is necessary to first raise the temperature of the particulate filter 50 to at least the fixed temperature T_0 and then maintain the temperature of the particulate filter 50 at least at the fixed temperature T_0 .

[0095] Therefore, in this embodiment as well, the various injection patterns shown in Fig. 12 are used for raising the temperature of the particulate filter 50 to at least the fixed temperature T_0 so as to regenerate the particulate filter 50. In this case, however, TC shows the temperature of the particulate filter 50. Further, in this embodiment, when maintaining the temperature of the particulate filter 50 at least at the fixed temperature T_0 , the injection pattern determined based on Fig. 24 is used. That is, when the temperature of the particulate filter 50 is to be held at least at the fixed temperature T_0 , injection is performed by the first injection pattern Q_R shown by (II) in Fig. 8 to Fig. 10 in the limited operating region where the required torque TQ is high and the engine rotational speed N is high and injection is performed by the second injection pattern $Q_V + Q_R$ shown by (III) in Fig. 8 or (III) in Fig. 9 in the remaining greater portion of the operating region. Note that in this embodiment, when the temperature of the particulate filter 50 is to be held at least at the fixed temperature T_0 , the air-fuel ratio of the exhaust gas is maintained lean.

[0096] Next, an explanation will be given of the operational control while referring to Fig. 25.

[0097] Referring to Fig. 25, first, at step 400, it is determined if a regeneration flag showing that the particulate filter 50 should be regenerated has been set. When the regeneration flag has not been set, the routine proceeds to step 401, where the ordinary operation is performed.

[0098] That is, at step 401, the target degree of opening ST of the throttle valve 17 is calculated from the map

shown in Fig. 5A and the degree of opening of the throttle valve 17 is made that target degree of opening ST. Next, at step 402, the target degree of opening SE of the EGR control valve 25 is calculated from the map shown in Fig. 5B and the degree of opening of the EGR control valve 25 is made that target degree of opening SE. Next, at step 403, the amount of injection Q is calculated from the map shown in Fig. 4A, the injection start timing θS is calculated from the map shown in Fig. 4B, and fuel is injected based on these calculated values. Next, at step 404, it is determined if the differential pressure ΔP before and after the particulate filter 50 is more than the maximum allowable value P_{max} based on the output signal of the differential pressure sensor 52, that is, if the amount of particulate matter deposited on the particulate filter 50 has exceeded a maximum allowable value. When $\Delta P > P_{max}$, that is, when the amount of particulate matter deposited on the particulate filter 50 has exceeded the maximum allowable value, the routine proceeds to step 405, where the regeneration flag is set.

[0099] When the regeneration flag is set, the routine proceeds to step 406, where the target degree of opening ST of the throttle valve 17 is calculated from the map shown in Fig. 5A and the degree of opening of the throttle valve 17 is made this target degree of opening ST. Next, at step 407, the target degree of opening SE of the EGR control valve 25 is calculated from the map shown in Fig. 5B and the degree of opening of the EGR control valve 25 is made this target degree of opening SE.

[0100] Next, at step 408, it is determined if a temperature raising completion flag showing that the particulate filter 50 has been raised to a temperature enabling ignition of the particulate matter on the particulate filter 50 has been set. When the regeneration flag has been set, normally the temperature raising completion flag is reset, therefore the routine proceeds to step 500, where the control for raising the temperature is performed. This control for raising the temperature is shown in Fig. 26.

[0101] Referring to Fig. 26, first, at step 501, it is determined if the temperature TC of the particulate filter 50 detected by the temperature sensor 39 is lower than the first temperature T1. When $TC < T1$, the routine proceeds to step 502, where injection is performed by the injection pattern determined based on (1) of Fig. 12.

[0102] On the other hand, when it is determined at step 501 that $TC \geq T1$, the routine proceeds to step 503, where it is determined if the temperature TC of the particulate filter 50 detected by the temperature sensor 39 is lower than the second temperature T2. When $TC < T2$, the routine proceeds to step 504, where injection is performed by the injection pattern determined based on (2) of Fig. 12.

[0103] On the other hand, when it is determined at step 503 that $TC \geq T2$, the routine proceeds to step 505, where injection is performed by the injection pattern determined based on (3) of Fig. 12. Next, at step 506, it is determined if the temperature TC of the particulate filter

50 detected by the temperature sensor 39 has become higher than the targeted fixed temperature T_0 . When $TC \geq T_0$, the routine proceeds to step 507, where the temperature raising completion flag is set.

[0104] Returning again to Fig. 25, when the temperature raising completion flag has been set, the routine proceeds to step 409, where the temperature of the particulate filter 50 is held at least at the fixed temperature T_0 . That is, at this time, injection is performed by the injection pattern determined based on Fig. 24. Next, at step 410, it is determined if the differential pressure ΔP before and after the particulate filter 50 has become lower than a minimum value P_{min} based on the output signal of the differential pressure sensor 52, that is, if all of the particulate matter deposited on the particulate filter 50 has been burned. When $\Delta P < P_{min}$, the routine proceeds to step 411, where the regeneration flag and the temperature raising completion flag are reset.

[0105] Note that it is also possible to arrange a catalyst having an oxidation function such as an oxidation catalyst or a three-way catalyst inside the exhaust passage upstream or downstream of the NO_x absorbent 22 in the first embodiment and inside the exhaust gas upstream or downstream of the particulate filter 50 in the second embodiment.

[0106] According to the present invention, as explained above, it is possible to raise the temperature of an exhaust gas after-treatment device at a temperature raising rate required for the exhaust gas after-treatment device.

[0107] While the invention has been described by reference to specific embodiments chosen for purposes of illustration, it should be apparent that numerous modifications could be made thereto by those skilled in the art without departing from the basic concept and scope of the invention.

[0108] An engine comprising an exhaust gas after-treatment device arranged in an exhaust passage of the engine, which raises the temperature of the exhaust gas after-treatment device by making selective use of a first injection pattern injecting only main fuel and delaying the injection timing of the main fuel Q_R , a second injection pattern injecting auxiliary fuel Q_V near top dead center of the suction stroke and delaying the injection timing of the main fuel Q_R , and a third injection pattern injecting auxiliary fuel Q_V and Q_P before injection of the main fuel and after injection and delaying the injection timing of the main fuel Q_R .

Claims

1. An internal combustion engine having a combustion chamber and an exhaust passage, said engine comprising:

fuel injection means for injecting an auxiliary fuel into the combustion chamber, in addition to

a main fuel, in accordance with necessity to produce unburned hydrocarbons;

an exhaust gas after-treatment device arranged in the exhaust passage, a temperature of said exhaust gas after-treatment device rising when a temperature of exhaust gas rises and rising when unburned hydrocarbons are supplied to said exhaust gas after-treatment device; and

injection control means for retarding an injection timing of the main fuel when the temperature of the exhaust gas after-treatment device should rise, as compared with the case where the temperature of the exhaust gas after-treatment device should not rise, at least two injection patterns, which are different in at least one of an amount of retardation of the injection timing of the main fuel and injection timing of the auxiliary fuel, being determined in advance to raise the temperature of the exhaust gas after-treatment device, said injection control means choosing any one of the injection patterns in accordance with a demand for a temperature raising rate of the exhaust gas after-treatment device and injecting fuel in accordance with the chosen injection pattern when the temperature of the exhaust gas after-treatment device should rise.

2. An internal combustion engine as set forth in claim 1, wherein at least two injection patterns are preset for raising the temperature of the exhaust gas after-treatment device from among a first injection pattern delaying the injection timing of the main fuel without injecting the auxiliary fuel, a second injection pattern injecting the auxiliary fuel before injection of the main fuel and delaying the injection timing of the main fuel, a third injection pattern injecting the auxiliary fuel before injection of the main fuel and after injection of the main fuel and delaying the injection timing of the main fuel, and a fourth injection pattern injecting the auxiliary fuel after injection of the main fuel and delaying the injection timing of the main fuel, and said injection control means selects one of the injection patterns from among the preset injection patterns and injects the main fuel and auxiliary fuel in accordance with the selected injection pattern.
3. An internal combustion engine as set forth in claim 2, wherein, in the first injection pattern, the injection timing of the main fuel is delayed until after top dead center of the compression stroke.
4. An internal combustion engine as set forth in claim 2, wherein, in the second injection pattern, the auxiliary fuel is injected near top dead center of the suction stroke and the amount of retardation of the in-

jection timing of the main fuel is made larger than the amount of retardation of the injection timing of the main fuel in the first injection pattern.

5. An internal combustion engine as set forth in claim 4, wherein the auxiliary fuel is injected when an exhaust valve is open.
6. An internal combustion engine as set forth in claim 4, wherein the injection timing of the auxiliary fuel is determined so that the injected auxiliary fuel is directed to a cavity formed in a top face of a piston.
7. An internal combustion engine as set forth in claim 2, wherein, in the second injection pattern, the auxiliary fuel is injected during the compression stroke and the amount of retardation of the injection timing of the main fuel is made larger than the amount of retardation of the injection timing of the main fuel in the first injection pattern.
8. An internal combustion engine as set forth in claim 7, wherein the injection timing of the auxiliary fuel is determined so that the injected auxiliary fuel is directed to a cavity formed in a top face of a piston.
9. An internal combustion engine as set forth in claim 2, wherein, in the third injection pattern, first auxiliary fuel is injected near top dead center of the suction stroke, second auxiliary fuel is injected during the expansion stroke or exhaust stroke, and the amount of retardation of the injection timing of the main fuel is made larger than the amount of retardation of the injection timing of the main fuel in the first injection pattern.
10. An internal combustion engine as set forth in claim 9, wherein the first auxiliary fuel is injected when an exhaust valve is open.
11. An internal combustion engine as set forth in claim 9, wherein the injection timing of the first auxiliary fuel is determined so that the injected auxiliary fuel is directed to a cavity formed in a top face of a piston.
12. An internal combustion engine as set forth in claim 9, wherein the second auxiliary fuel is injected during an expansion stroke before an exhaust valve opens.
13. An internal combustion engine as set forth in claim 9, wherein the second auxiliary fuel is injected at intervals over several times.
14. An internal combustion engine as set forth in claim 2, wherein, in the third injection pattern, the first auxiliary fuel is injected during the compression stroke,

the second auxiliary fuel is injected during the expansion stroke or exhaust stroke, and the amount of retardation of the injection timing of the main fuel is made larger than the amount of retardation of the injection timing of the main fuel in the first injection pattern.

15. An internal combustion engine as set forth in claim 14, wherein the injection timing of the first auxiliary fuel is determined so that the injected auxiliary fuel is directed to a cavity formed in a top face of a piston.
16. An internal combustion engine as set forth in claim 14, wherein the second auxiliary fuel is injected during the expansion stroke before an exhaust valve opens.
17. An internal combustion engine as set forth in claim 14, wherein the second auxiliary fuel is injected at intervals over several times.
18. An internal combustion engine as set forth in claim 2, wherein, in the fourth injection pattern, the injection timing of the main fuel is delayed until after the top dead center of the compression stroke and the auxiliary fuel is injected during the expansion stroke or exhaust stroke.
19. An internal combustion engine as set forth in claim 18, wherein the auxiliary fuel is injected during the expansion stroke before an exhaust valve opens.
20. An internal combustion engine as set forth in claim 18, wherein the auxiliary fuel is injected at intervals over several times.
21. An internal combustion engine as set forth in claim 2, wherein when the temperature of the exhaust gas after-treatment device should be raised, while the temperature of the exhaust gas after-treatment device is rising, the injection pattern is switched in accordance with need from the third injection pattern to the second injection pattern, from the second injection pattern to the first injection pattern, or from the third injection pattern to the second injection pattern to the first injection pattern.
22. An internal combustion engine as set forth in claim 2, wherein when the temperature of the exhaust gas after-treatment device should be raised, which of the injection patterns to use is determined in accordance with the temperature of the exhaust gas after-treatment device.
23. An internal combustion engine as set forth in claim 2, wherein when the temperature of the exhaust gas after-treatment device should be raised, which of

the injection patterns to use is determined in accordance with the temperature of the exhaust gas after-treatment device and the operating state of the engine.

24. An internal combustion engine as set forth in claim 23, wherein a first operating region where fuel is injected by the first injection pattern, a second operating region where fuel is injected by the second injection pattern, and a third operating region where fuel is injected by the third injection pattern are preset in accordance with the temperature of the exhaust gas after-treatment device and the operating state of the engine.
25. An internal combustion engine as set forth in claim 24, wherein when the temperature of the exhaust gas after-treatment device is lower than a predetermined temperature, the majority of the operating region becomes the third operating region and when the temperature of the exhaust gas after treatment device becomes higher than the predetermined temperature, the third operating region is reduced to a smaller region on the low load side.
26. An internal combustion engine as set forth in claim 25, wherein the second operating region is positioned at the high load side of the third operating region and when the temperature of the exhaust gas after-treatment device becomes higher, the second operating region shifts to the low load side.
27. An internal combustion engine as set forth in claim 26, wherein the first operating region is positioned at the high load side of the second operating region and when the temperature of the exhaust gas after-treatment device becomes higher, the first operating region shifts to the low load side.
28. An internal combustion engine as set forth in claim 1, wherein the exhaust gas after-treatment device comprises an NO_x absorbant which absorbs NO_x when an air-fuel ratio of the exhaust gas is lean and releases the NO_x when the air-fuel ratio of the exhaust gas becomes the stoichiometric air-fuel ratio or rich and the temperature of the NO_x absorbant is raised when SO_x is to be released from the NO_x absorbant.
29. An internal combustion engine as set forth in claim 28, wherein the air-fuel ratio of the exhaust gas is made the stoichiometric air-fuel ratio or rich so as to release the SO_x from the NO_x absorbant after the temperature of the NO_x absorbant exceeds a predetermined target temperature.
30. An internal combustion engine as set forth in claim 29, wherein intake air control means is provided for

controlling an amount of intake air and, when SO_x is to be released from the NO_x absorbant, the amount of intake air is reduced by the intake air control means, the injection timing of the main fuel is delayed compared with when the temperature of the NO_x absorbant should not be raised, and the auxiliary fuel is injected during the expansion stroke or exhaust stroke, whereby the air-fuel ratio of the exhaust gas is made the stoichiometric air-fuel ratio or rich.

31. An internal combustion engine as set forth in claim 30, wherein said auxiliary fuel is injected during an expansion stroke before an exhaust valve opens.
32. An internal combustion engine as set forth in claim 30, wherein the auxiliary fuel is injected at intervals over several times.
33. An internal combustion engine as set forth in claim 1, wherein the exhaust gas after-treatment device comprises a particulate filter for trapping particulate matter contained in the exhaust gas and the temperature of the particulate filter is raised when the particulate matter trapped by the particulate filter is to be burned.
34. An internal combustion engine as set forth in claim 33, wherein when the temperature of the particulate filter exceeds a predetermined temperature, the particulate matter trapped by the particulate filter is burned and, when the particulate matter is burned, the injection timing of the main fuel is delayed compared with when the temperature of the particulate filter should not be raised and the auxiliary fuel is injected before the injection of the main fuel.
35. An internal combustion engine as set forth in claim 34, wherein said auxiliary fuel is injected near top dead center of the suction stroke.
36. An internal combustion engine as set forth in claim 34, wherein said auxiliary fuel is injected during a compression stroke.

Fig.1




Fig.2A




Fig.2B




Fig.3




Fig.4A




Fig.4B




Fig.5A




Fig.5B




Fig.6A




Fig.6B




Fig.7




Fig.8




Fig.9




Fig.10




Fig.11




Fig.12






Fig.13A




Fig. 13B




Fig.14




Fig.15




Fig.16A




Fig.16B




Fig.17




Fig.18




Fig.19




Fig.20




Fig. 21




Fig.22




Fig. 23




Fig. 24




Fig.25






Fig.26





Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 108 876 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
24.09.2003 Bulletin 2003/39

(51) Int Cl.7: **F02D 41/40, F01N 3/20,
F02D 21/08, F02D 41/02**

(43) Date of publication A2:
20.06.2001 Bulletin 2001/25

(21) Application number: 00101967.8

(22) Date of filing: 01.02.2000

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Ito, Takekazu
Toyota-shi, Aichi-ken 471-8571 (JP)
• Sasaki, Shizuo
Toyota-shi, Aichi-ken 471-8571 (JP)

(30) Priority: 16.12.1999 JP 35771899


(71) Applicant: **TOYOTA JIDOSHA KABUSHIKI
KAISHA**
Aichi-ken 471-8571 (JP)

(74) Representative:
Pellmann, Hans-Bernd, Dipl.-Ing. et al
Patentanwaltsbüro
Tiedtke-Bühling-Kinne & Partner
Bavariaring 4-6
80336 München (DE)

(54) **Internal combustion engine**

(57) An engine comprising an exhaust gas after-treatment device arranged in an exhaust passage of the engine, which raises the temperature of the exhaust gas after-treatment device by making selective use of a first injection pattern injecting only main fuel and delaying the injection timing of the main fuel Q_R , a second injection pattern injecting auxiliary fuel Q_v near top dead center of the suction stroke and delaying the injection timing of the main fuel Q_R , and a third injection pattern injecting auxiliary fuel Q_v and Q_p before injection of the main fuel and after injection and delaying the injection timing of the main fuel Q_R .

Fig.1





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 10 1967

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
E	EP 1 026 385 A (TOYOTA MOTOR CO LTD) 9 August 2000 (2000-08-09) * the whole document *	1-36	F02D41/40 F01N3/20 F02D21/08 F02D41/02
E	EP 1 086 304 A (PEUGEOT CITROEN AUTOMOBILES SA) 28 March 2001 (2001-03-28) * the whole document *	1, 33, 34, 36	
E	EP 1 035 315 A (MAZDA MOTOR) 13 September 2000 (2000-09-13) * paragraphs [0061],[0084]; figures 1, 14, 21 *	1, 2, 28, 29	
X	US 5 967 113 A (KUWABARA KAZUNARI ET AL) 19 October 1999 (1999-10-19) * column 7, line 54 - column 16, line 39; figures 1, 4, 5, 7 *	1	
A		2, 28	
X	EP 0 916 829 A (DAIMLER CHRYSLER AG) 19 May 1999 (1999-05-19) * the whole document *	1-3, 18, 20, 22, 23 28	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
X	EP 0 321 451 A (MITSUBISHI MOTORS CORP) 21 June 1989 (1989-06-21) * page 6, line 1 - page 15, line 43; figures *	1, 28, 29, 33 2	F02D
A	EP 0 862 941 A (TOYOTA MOTOR CO LTD) 9 September 1998 (1998-09-09) * column 14, line 4 - column 21, line 8; figures 5-7 *	1, 28, 29	
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 1 August 2003	Examiner Aign, T
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document</p> <p>T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P4C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 10 1967

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-08-2003

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 1026385	A	09-08-2000	JP	3225957 B2	05-11-2001
			JP	2000291462 A	17-10-2000
			EP	1026385 A2	09-08-2000
			US	6276130 B1	21-08-2001
EP 1086304	A	28-03-2001	FR	2792036 A1	13-10-2000
			EP	1086304 A1	28-03-2001
			JP	2002541373 T	03-12-2002
			US	6412276 B1	02-07-2002
			WO	0060228 A1	12-10-2000
EP 1035315	A	13-09-2000	JP	2000320386 A	21-11-2000
			EP	1035315 A2	13-09-2000
US 5967113	A	19-10-1999	JP	3257423 B2	18-02-2002
			JP	10169488 A	23-06-1998
			DE	19755348 A1	01-10-1998
			KR	241045 B1	02-03-2000
EP 0916829	A	19-05-1999	DE	19750226 C1	29-10-1998
			EP	0916829 A2	19-05-1999
			US	6082325 A	04-07-2000
EP 0321451	A	21-06-1989	JP	1745288 C	25-03-1993
			JP	4029845 B	20-05-1992
			JP	60206922 A	18-10-1985
			JP	60206923 A	18-10-1985
			JP	1745289 C	25-03-1993
			JP	4029846 B	20-05-1992
			JP	60216018 A	29-10-1985
			JP	1745291 C	25-03-1993
			JP	4029847 B	20-05-1992
			JP	60224914 A	09-11-1985
			JP	1844374 C	25-05-1994
			JP	5024326 B	07-04-1993
			JP	60228720 A	14-11-1985
			JP	1745294 C	25-03-1993
			JP	4029848 B	20-05-1992
			JP	61049116 A	11-03-1986
			JP	61093222 A	12-05-1986
			JP	61093236 A	12-05-1986
			JP	61112717 A	30-05-1986
			JP	61116013 A	03-06-1986
			EP	0321451 A2	21-06-1989
			DE	3580606 D1	03-01-1991
			EP	0158887 A2	23-10-1985

EPO FORM P0439

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 10 1967

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-08-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
EP 0321451	A	KR 8903592 B1	25-09-1989	
		KR 8903593 B1	25-09-1989	
		KR 8903594 B1	25-09-1989	
		KR 8903595 B1	25-09-1989	
		US 4835964 A	06-06-1989	
		US 4719751 A	19-01-1988	

EP 0862941	A	09-09-1998	JP 10306717 A	17-11-1998
			DE 69807370 D1	02-10-2002
			EP 0862941 A2	09-09-1998
			US 5974791 A	02-11-1999

EPO FORM P0469

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82